





Established in 1980, the Nectre brand has long been recognised as a honest and reliable wood heater that produces stunning warmth and comfort from a timeless design with easy to operate features. Today, that Nectre warmth and comfort is enjoyed in well over 7 countries.

We are proud of our tradition, history and even more so to be one of the leading Australian wood heater manufacturers. We strive to make the very best heater for value while providing excellent all-round performance. We are driven daily to achieve manufacturing excellence and as such every Nectre wood heater meets or exceeds AS/NZS 4012:2014 and AS/NZS 4013:2014 standards.

The famous Australian Made® logo is the true mark of Aussie authenticity and is Australia's most trusted, recognised and widely used country of origin symbol, underpinned by a third-party accreditation system, which ensures products that carry the logo are certified as 'genuinely Australian'.

Nectre heaters are designed and manufactured right here in Australia, delivering rock-solid build quality, exceptional heating performance and timeless classic design to all Australians.

Nectre FORM 1



A fresh and novel take on what a combustion heater can look like, and the only wood heater in the Australian wood heating landscape with its narrow yet deep form factor. The sleek capsule shape is resolved with cast iron, high quality stainless steel controls and curved glass, which offers a wider view of the flames, impressive performance and heating efficiency. The outside air capability and ability to cook on the top plate will make Form 1 especially attractive for compact, eco-friendly housing designs, and make it a better fit for newly constructed housing in general.

SPECIFICATIONS

Coverage	Up to 90m2
Heat Output	Max ave. 7kW
Efficiency	70%
Emissions	0.70g/kg
Firebox size	235(w) x 365(d) x 270(h)
Max log width	340
Weight	80kg
Heating style	Radiant



PEDESTAL



Size: 300(w) x 550(d) x 600(h)



Nectre FORM 2



Designed to suit the modern Australian, it is not only clean and extremely modern in its aesthetics but performs exceptionally well with low emissions and powerful heat output. The ability to connect the air intake of the heater to an outside air source, will mean that it can efficiently heat the modern Australian home. A cast iron door and top plate not only resonate the robust quality synonymous with the Nectre brand but also more effectively radiate heat into the home. A large pane of curved, flame-resistant glass gives a more captivating view of the fire.

SPECIFICATIONS

Coverage	Up to 180m2
Heat Output	Max ave. 13kW
Efficiency	65%
Emissions	0.60g/kg
Firebox size	335(w) x 295(d) x 365(h)
Max log width	330mm
Weight	146kg
Heating style	Convection



WOODSTACKER



Size: 520(w) x 464.4(d) x 1103(h)



Nectre N15



Working with a smaller space? The Nectre N15 is a simple, classic and compact solution that offers an impressive radiant heating capacity of up to 160m2. Add some wood fire magic to any corner of the room. Get cosy and enjoy.

SPECIFICATIONS

Coverage	Up to 160m2
Heat Output	Max ave. 13kW
Efficiency	79%
Emissions	1.3g/kg
Firebox size	370(w) x 320(d) x 320(h)
Max log width	330
Weight	90kg
Heating style	Radiant





Size: 462(w) x 515(d) x 664(h)

PEDESTAL









The Nectre NGO is a clean burning wood heater. Together with great looks and easy to use functions the NGO is a favourite and fits beautifully in either a traditional or contemporary living area.

SPECIFICATIONS

Coverage	Up to 170m2
Heat Output	Max ave. 11kW
Efficiency	73%
Emissions	0.60g/kg
Firebox size	345(w) x 275(d) x 450(h)
Max log width	300mm
Weight	190kg
Heating style	Radiant/ Convection



*All dimensions are in millimeters (mm) unless specified otherwise and are shown without side shields fitted (if available). In the interest of product development, Glen Dimplex Australia Pty Ltd reserve the right to change product specifications without prior notice. Refer to the IOM online for the latest up to date information.

Size: 454(w) x 510(d) x 1041(h)

NAKED

Nectre MK1



The Nectre Mk1 is one of the best performing radiant heaters for output, coverage and efficiency. The Mk1 is right at home in any living space while providing charm, warmth and comfort. Easy to operate features makes it one of our favourite heaters.

SPECIFICATIONS

Coverage	Up to 200m2
Heat Output	Max ave. 19kW
Efficiency	73%
Emissions	0.95g/kg
Firebox size	580(w) x 315(d) x 340(h)
Max log width	500mm
Weight	115kg/ 120kg
Heating style	Radiant





Size: 725(w) x 510(d) x 664(h)

PEDESTAL







Nectre MK2



The Nectre Mk2 is a simple but elegant radiant/ convection heater that circulates warmth effectively throughout any living space. Mk2 pushes out an impressive peak 20kW.

SPECIFICATIONS

Coverage	Up to 200m2
Heat Output	Max ave. 18kW
Efficiency	73%
Emissions	0.80g/kg
Firebox size	515(w) x 305(d) x 330(h)
Max log width	450
Weight	140kg/ 160kg
Heating style	Radiant/ Convection
*Optional 3 speed	fan for pedestal only



*All dimensions are in millimeters (mm) unless specified otherwise and are shown without side shields fitted (if available). In the interest of product development, Glen Dimplex Australia Pty Ltd reserve the right to change product specifications without prior notice. Refer to the IOM online for the latest up to date information.

LEGS



Size: 750(w) x 528(d) x 653(h)

PEDESTAL



Size: 750(w) x 528(d) x 716(h)



The Nectre Mk3 is built with an approved wood stack base together with deeper firebox which makes it not only look good but performs brilliantly as a radiant/convection hardwood heater. Standard remote control 3 speed fan is a welcome addition.

SPECIFICATIONS

Coverage	Up to 270m2
Heat Output	Max ave. 18kW
Efficiency	62%
Emissions	1.1g/kg
Firebox size	530(w) x 400(d) x 330(h)
Max log width	450
Weight	160kg
Heating style	Radiant/ Convection
*O apped permete	antral far arman an atandar

*3 speed remote control fan comes as standard







Size: 750(w) x 627(d) x 792(h)



The MEGA is designed to cover larger living spaces and provide superb warmth from its radiant convection design, fitting well in both traditional and contemporary styles.

SPECIFICATIONS

Coverage	Up to 340m2
Heat Output	Max ave. 22kW
Efficiency	62%
Emissions	1.5g
Firebox size	600(w) x 430(d) x 320(h)
Max log width	500
Weight	170kg/ 180kg
Heating style	Radiant/ Convection
*Optional 3 speed	fan for pedestal model only



*All dimensions are in millimeters (mm) unless specified otherwise and are shown without side shields fitted (if available). In the interest of product development, Glen Dimplex Australia Pty Ltd reserve the right to change product specifications without prior notice. Refer to the IOM online for the latest up to date information.

LEGS



Size: 760(w) x 632(d) x 798(h)

PEDESTAL



Size: 760(w) x 632(d) x 801(h)

Nectre **INBUILT**



The Nectre Inbuilt delivers natural convection warmth with all the charm and comfort you expect from a Nectre. Nectre Inbuilt is an all-round performer with the style and easy to use functions and it will fit into most existing fireplaces.

SPECIFICATIONS

Coverage	Up to 160m2
Heat Output	Max ave. 10kW
Efficiency	62%
Emissions	0.90g/kg
Firebox size	500(w) x 325(d) x 370(h)
Max log width	430mm
Weight	120kg
Heating style	Radiant/ Convection
*3 sneed remote	control fan comes as standard

*3 speed remote control fan comes as standard



INBUILT



Size: 695(w) x 541(d) x 578(h)

Nectre N900

SEAL LASS



The Nectre N900 is one of the largest open fronted, wood burning fireplaces on the market. It offers versatility in its installation, in either a freestanding woodstacker or a built-in, with the option for masonry installation. The N900 can become the centrepiece of any room or undercover alfresco area.

SPECIFICATIONS

Coverage	Up to 100m2
Heat Output	Up to 15kW
Firebox size	880(w) x 340(d) x 320(h)
Max log width	600
Weight	Up to 250kg
Heating style	Convection
*3 speed remote control fan comes as standard	

WOODSTACKER



Size: 1037(w) x 625(d) x 1128(h)

INBUILT







Nectre **BAKERS OVEN**



The Nectre Bakers Oven provides excellent warmth and cooking performance. With a small footprint it fits in just about any living space without being obtrusive. The cook top adds a warming or direct cooking option with removable rings.

SPECIFICATIONS

Coverage	Up to 120m2
Heat Output	Up to 11kW
Firebox size	340(w) x 300(d) x 380(h)
Max log width	300
Weight	120kg
Heating style	Radiant
*Optional factory fitted domestic hot water booster	

FREESTANDING



Size: 550(w) x 573(d) x 823(h)



Nectre BIG BAKERS OVEN



The Nectre Big Bakers Oven produces amazing radiant warmth and coverage. Designed with character and charm the Big Bakers Oven provides a spacious oven for those Sunday roasts. The cook top adds a warming or direct cooking option with removable rings.

SPECIFICATIONS

Coverage	Up to 200m2
Heat Output	Up to 14kW
Firebox size	485(w) x 295(d) x 300(h)
Max log width	445
Weight	220kg
Heating style	Radiant
*Optional factory	fitted domestic hot water booster

*Optional factory fitted domestic hot water booster

FREESTANDING




Size: 690(w) x 577(d) x 823(h)



How to Choose a Wood Heater?

Taking the time to understand how a wood heater works and your heating requirements.



RADIANT HEATERS

(Nectre Form 1, Mk1 & N15)

A radiant heater does not have any outer casings on the firebox except for a rear heatshield. A radiant heater will heat the objects in the room in a straight line from the heater, like an electric bar radiator. Radiant heaters are ideal for rooms with high ceilings and used in conjunction with a ceiling fan is a very effective method of heating. A radiant heater will require a larger clearance to the sides than a convection style heater.

RADIANT / CONVECTION HEATER

(Nectre Form 2, Mk2, Mk3, Mega, N60, & Inbuilt)

A radiant/convection heater will emit radiant heat from the front of the heater and the lower top, front step but has a convection chamber built into the sides and rear of the appliance which allows for the addition of a fan to increase the speed of this convection air. The side clearances are also reduced because of these air gaps. A natural convection is created through this chamber depending on the burn rate of the fire but an optional fan can be added to increase the speed of this air movement. No fan available for the N60.

Maintaining a wood fire heater is easier than you may think. Other things to consider are ensuring that the wood you burn is dry, that you regularly clean out the ash when it is cold and keeping the glass door clean.

Nectre Flue Requirements

The flue system used when installing a Nectre must comply with the current installation standards of AS/NZS 2918. Full instructions on the installation of the flue will be supplied with the flue kit and these must be adhered to. The minimum exit height from the top of the floor protector (hearth) must not be less than 4.6m and the minimum exit height above the roof line of the roof ridge as detailed in the instructions.

SUITABLE FLUE SHIELD CONFIGURATION



REAR SHIELD

900mm length, minimum 160° arc, stainless steel rear flue shield, can be painted black.

Models suitable for FORM 1 | FORM 2 | N15 | Mk1 | Mk2 | Mk3 | Mega | N60| Bakers Ovens



DECROMESH

Decromesh with 900mm inner reflector fitted with DLR Models suitable for

N15 | Mk1 | Mk2 | Mk3 | Mega | N60

Decromesh with no inner reflector fitted with DLR

Models suitable for FORM 1 | FORM 2



SOLID

200mm Solid flue outer with 900mm inner reflector fitted with DLR

Model suitable for FORM 2 | N15 | Mk1 | Mk2 | Mk3 | Mega | N60

200mm Solid flue outer with no inner reflector fitted with DLR


Model suitable for FORM 1



Decromesh Locating Ring (DLR) is supplied with all models where required



4.6m Flue from the hearth plus the minimum above the roof line of the roof ridge.



BurnWise

For the very best performance out of a Nectre wood heater, we recommend only burning dry seasoned hardwood. Pre-season maintenance check and a possible flue clean will ensure excellent Nectre performance. Avoid using salt borne drift wood, pine and/or chemically treated woods.



Nectre Product Reference Guide

			Gadot									
			Form 1	Form 2		N15		NE	50	M	<1	
Туре			Radiant	Convection	Radiant			Radiant / Convection		Radiant		
Style Conter			Contemporary	Contemporary	Traditional			Conten	Contemporary		ional	
		Base	Pedestal	Woodstacker	Legs Woodstacker Pedestal			Naked Curved		Legs Pedestal		
		Colour	Black	Black	Black			Black		Black		
	Test	ted with Fan	No	No	No			No		N	0	
	Output	Peak	8.7	15.2		15		1	3	2	2	
Ce	(Kilowatts)	Ave.	7	13		13		1	11		9	
Performance	Emissions		0.70	0.60		1.3		0.0	60	0.9	95	
μu	Efficiency (%)	Peak	74	71.5		86		8	4	8	1	
irfc	Emolency (70)	Ave.	70	65		79		7	3	7	3	
Pe	Coverage	squares	10	19		13-17		14-18		18-	22	
	0010.000	m²	90	180		120-160		130-	-170	170-	200	
		kg	80	146	90	127	90	190	190	115	120	
υO	Heater Size	(w)	300	520	460	460	460	454	581	725	725	
ati		(d)	550	464.4	450	450	450	485	485	420	420	
fic		(h)	600	1103	665	905	730	1037	1037	690	725	
Specification	Log Size (max)	mm	340	330		330		30	00	50	00	
Sp	Firebox size	m ³	0.023	0.036		0.038		0.0	143	0.0	62	
	Fabricated	Steel	4, 5 & 6	4, 5 & 6		6		E	3	E	5	
		(w)	594	725	900	900	900	72	20	90	0	
	Hearth (min)	(d)	850	764.4	900	900	900	74	10	90		
	-	Thickness	5	5	15	15	15	7.	5	1	5	
	900mm Rear Flue Shield	Rear	100	150	175	175	175	75	100	14	10	
		Side	550	500	750	750	750	450	190	65	50	
		Corner	300	200	750	750	750	225	125	50	0	
	-	Front	300	300	300	300	300	30	00	40	0	
	900mm Rear Flue Shield + Side Shields	Rear			125	240	125			14	10	
		Side			450	550	450			50	500	
		Corner			225	300	225			30	0	
		Front			300	300	300			40	00	
	Decro-mesh	Rear	100	125								
		Side	550	500								
a		Corner	300	200								
Clearance		Front	300	300								
ara		Rear			175	175	175	125	150	14	10	
Clea	Decro-mesh	Side			750	750	750	450	150	65	i0	
	with 900mm Inner Reflector	Corner			750	750	750	225	125	50	00	
		Front			300	300	300	30	00	40	00	
	Deers	Rear			175	240	175			14	10	
	Decro-mesh with 900mm	Side			450	550	450	450		500		
	Inner Reflector + Side Shields	Corner			225	300	225			27		
		Front			300	300	300			40	00	
	200mm Solid Flue Outer	Rear	100									
		Side	550									
		Corner	300									
		Front	300									
	200mm Solid Flue Outer with 900mm Inner Reflector	Rear		125	175	240	175	125	150	14		
		Side		500	750	550	750	450	150	65		
		Corner		200	750	300	750	225	125	50		
		Front		300	300	300	300	30	00	40	00	
	Fan (manual)	3 Speed										
SU	Fan (remote)	3 Speed										
Options	Shields	Side			Yes					Ye	s	
0 D	Trivet	Cast				Yes						
	Air Connection	Outside	Yes	Yes								

Nectre Product Reference Guide

		Mk2		Mk3	MEGA		Inbuilt		Bakers Oven		
Туре			Radiant / Convection		Radiant / Convection	Radiant / Convection		Radiant / Convection		Radiant	
		Style	Traditional		Traditional	Traditional		Traditional		Traditional	
		Base	Legs	Pedestal	Woodstacker	Legs	Pedestal	-		Original BIG	
Colour			Black		Black	Bla	ack	Black		Black	
Tested with Fan		No Yes		Yes	No	Yes	Yes		No		
	Output (Kilo-	Peak	2	20	21	20	25	1	3	15	18
ЭС	watts)	Ave.	,	18	18	16	22	1	D	11	14
Performance	Emissions		0.80	1.3	1.1	1.5	1.5	0.9	90	N	/A
ող		Peak	67	79	66	65	65	7	D	N	/A
rfo	Efficiency (%)	Ave.	61	73	62	62	62	6	2	N	/A
Pe	2	squares	18	-22	24-28	30	-37	13-	17	8-13	17-22
	Coverage	m²	170	-200	240-270	280	-340	120-	160	75-120	160-200
		kg	140	160	160	170	180	12	20	120	220
UC		(w)	750	750	750	760	760	65	15	550	690
atic	Heater Size	(d)	445	445	541	540	540	54	1	535	535
fice		(h)	680	745	820	826	826	57	'8	825	825
eci	Log Size (max)	mm	4	50	450	50	00	43	10	300	445
Specification	Firebox size	m ³	0.1	052	0.070	0.0)82	0.0	50	0.039	0.043
	Fabricated	Steel		6	6 & 8	68	3.8	E	;	6	6&8
	Hearth (min)	(w)	900		900	900		900		900	900
		(d)	900		900	90	00	400	300	900	900
		Thickness	15		15	1	5	40	110	12	15
	900mm Rear	Rear	1	25	150	200				125	125
		Side	4	50	400	87	75			350	325
a	Flue Shield	Corner	2	00	150	45	50			350	275
nc		Front	400	350	300	30	00	400	300	300	300
ana		Rear	1	25	150	20	00				
Clearance	Decro-mesh with 900mm	Side	3	50	400	875					
	Inner Reflector	Corner	1	25	150	45	50				
		Front	400	350	300	30	00				
	200mm Solid Flue Outer with	Rear	1	25	150	200					
		Side	350		400	800					
	900mm Inner Reflector	Corner		00	125	45	50				
		Front	400	350	300	30	00				
S	Fan (manual)	3 Speed		Yes			Yes				
u o	Fan (remote)	3 Speed			Yes			Ye	s		
Options	Shields	Side									
Ο	Trivet	Cast									
				N900	n						

		NS	300						
	Туре	Open fronted					N900		
	Style	Contemporary				(w)	12	85	
	_	Woodstacker	Inbuilt	nce	Hearth (min)	(d)	1000	908-1108*	
	Base					Thickness	5-50**		
	Colour	Black				Rear	100	-	
Heater Size	(w)	10	1037			Side	500	-	
	(d)	625	608		NSOO FS Hue Kit	Corner	25	-	
	(h)	1128	649			Front	300***	-	
Log Size (max)	mm	600			N900 ZC flue kit	Side	-	550	
Firebox size	m³	0.075				Front	-	300-500***	
Fabricated	Steel	5			Fan (remote)	3 Speed	Yes		
	Log Size (max) Firebox size	Style Base Colour Heater Size (d) (h) Log Size (max) Mm Sirebox size	Type Open Style Conter Base Woodstacker Colour Modestacker Colour Colour Heater Size (M) (d) 625 (h) 1128 Log Size (max) mm Firebox size m³	Style Conterrary Base Woodstacker Inbuilt Colour Black Glack GOB Colour G1128 Glack G49 Log Size (max) mm Firebox size m³	Type Open rotted Style Conterrory Base Woodstacker Inbuilt Colour Base Colour Base	Type Open Function Style Contermany Image: Fireback size Hearth (min) Base Woodstacker Inbuilt Hearth (min) Color Base State size Hearth (min) Color Base State size Modstacker Inbuilt Hearth (min) Heater Size G(M) State size State size Moon Figure size Moon Figure size Log Size (max) Mm State size Moon Figure size Moon Figure size Firebox size Main State size Moon Figure size Moon Figure size	Type Open - treed Style Conter-verw $I = 0$	Type Open Fored Style Contermany Imbuilt Impute Impute<	

NOTE: Nectre Bakers Oven & Big Bakers Oven emissions and efficiency are shown as n/a, they are classified as a cooking stove and are exempt. All measurements are in millimeters (mm) and are correct at time of print. Glen Dimplex Australia Pty Ltd reserves the right to change or alter product specifications as required. *Dependent on how far the base of the firebox is from the floor

**Dependent on material used **May be reduced to 300mm if firebox is raised 450 above the floor, equivalent to woodstacker base cabinet

It is recommended that a qualified person/s carry out the installations in accordance to all specifications contained within this document, and with all relevant building codes. Glen Dimplex Australia Pty Ltd reserves the right to change or alter drawings, specifications or dimensions without prior notice. The information contained within the document was correct at time of printing.



"We make great wood heaters to suit contemporary and traditional living"



Glen Dimplex Australia Pty Ltd 8 Lakeview Drive, Scoresby, VIC 3179 **T** 1300 554 155

- E flame@glendimplex.com.au

Nectre is a registered trademark of Glen Dimplex Australia Pty Ltd, all rights reserved.

NECBRO23

nectre.com.au

Authorised Nectre Dealer